

# Technical data sheet

## Push-fit plug Delta-Push® for pushing in

Item number: 2351670



Push-fit plug Delta-Push® for mounting electrical installations. Suitable for concrete, calcareous limestone, full brick, hollow brick and porous concrete. Toolless mounting by pushing into a drill hole in a wall or on a ceiling. Without screws. To install cable trunking or labelling panels, for example.



PA

Polyamide

### Master data

|                     |                 |
|---------------------|-----------------|
| Item number         | 2351670         |
| Type                | DP D 30         |
| Description 1       | Push-fit plug   |
| Description 2       | for pressing in |
| Available from      | 01.02.2025      |
| Manufacturer        | OBO             |
| Dimension           | 34,2x14,2x12,2  |
| Material            | Polyamide       |
| Smallest sales unit | 100             |
| Unit of quantity    | Piece           |
| Weight              | 0.083 kg        |
| Weight unit         | kg/100 pc.      |


# Technical data sheet

## Push-fit plug Delta-Push® for pushing in

Item number: 2351670



### Dimensions



Length 30 mm

### Technical data

|                                        |                                                                                    |
|----------------------------------------|------------------------------------------------------------------------------------|
| Version for                            | Push-fit anchor                                                                    |
| Drill hole depth                       | 35 mm                                                                              |
| Drill hole diameter, max.              | 6 mm                                                                               |
| Drill hole diameter, min.              | 6 mm                                                                               |
| Suitable for fastening with cable ties | no                                                                                 |
| Suitable for gas concrete              | yes                                                                                |
| Suitable for hexagonal wood screw      | no                                                                                 |
| Halogen-free                           | yes                                                                                |
| With edge                              | no                                                                                 |
| With bolts                             | no                                                                                 |
| Mounting temperature, max.             | 60 °C                                                                              |
| Min. mounting temperature              | 5 °C                                                                               |
| Temperature-resistance, max.           | 60 °C                                                                              |
| Temperature resistance, min.           | -20 °C                                                                             |
| Suitable for material                  | Calcareous sandstone Porous concrete Concrete Gas concrete Full brick Hollow brick |
| Mounting type, anchor, tie             | Push-through mounting                                                              |

### Loads

|                                               |       |
|-----------------------------------------------|-------|
| Breaking load lime sandstone                  | 400 N |
| Safe working load concrete                    | 175 N |
| Safe working load vertically perforated brick | 130 N |
| Safe working load lime sandstone              | 175 N |
| Breaking load concrete                        | 400 N |
| Breaking load vertically perforated brick     | 300 N |